

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Product name : MXS STAINLESS STEEL SPRAY PAINT  
Vaporizer : Aerosol

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Paint

**1.3. Details of the supplier of the safety data sheet**

ATLANTİK AEROSOL ve KİMYA SANAYİ A.Ş.  
Fatih Mh. Altinkent Sk. No:4 Tavşanlı Beldesi Altınova  
Yalova - TÜRKİYE  
T + 90 226 465 72 27 - F + 90 226 465 72 26  
[info@atlantikkimya.com.tr](mailto:info@atlantikkimya.com.tr) - [www.atlantikaerosol.com](http://www.atlantikaerosol.com)

**1.4. Emergency telephone number**

Country	Organisation/Company	Address	Emergency number	Comment
Turkey	Ulusal Zehir Merkezi (UZEM) Refik Saydam Hıfzıssıhha Merkezi Başkanlığı	Cemal Gürsel Cd. No: 18 Sıhhiye Çankaya 06590 Ankara	114	Information is provided to public and medical personnel on poisoning incidents via 114.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

Aerosol, Category 1 H222;H229  
Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 1 H318  
Reproductive toxicity, Category 2 H361  
Specific target organ toxicity — Single exposure, Category 2 H371  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336  
Specific target organ toxicity — Repeated exposure, Category 2 H373


Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects : Pressurised container: May burst if heated. Extremely flammable aerosol. May cause damage to organs through prolonged or repeated exposure. May cause damage to organs. May cause drowsiness or dizziness. Causes skin irritation. Suspected of damaging fertility or the unborn child. Causes serious eye damage.

**2.2. Label elements**

Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

Hazard pictograms (SEA) :



Signal word (SEA) : Danger

Hazardous ingredients : toluene; acetone; propan-2-one; propanone; 2-methylpropan-1-ol; iso-butanol; n-butyl acetate; methanol; propan-2-ol; isopropyl alcohol; isopropanol

Hazard statements (SEA) :  
H222 - Extremely flammable aerosol.  
H315 - Causes skin irritation.  
H318 - Causes serious eye damage.  
H336 - May cause drowsiness or dizziness.  
H361 - Suspected of damaging fertility or the unborn child.  
H371 - May cause damage to organs.  
H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (SEA) : P201 - Obtain special instructions before use.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No



# MXS STAINLESS STEEL SPRAY PAINT

## Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 14/01/2019 Version: 0.0

smoking.

P251 - Do not pierce or burn, even after use.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face with soap and water thoroughly after handling

P270 - Do not eat, drink or smoke when using this product.

### 2.3. Other hazards

#### Other hazards not contributing to the classification

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.
Dimethyl ether	(CAS-No.) 115-10-6 (EC-No.) 204-065-8 (EC Index-No.) 603-019-00-8	40	Flam. Gas 1, H220 Press. Gas
Toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3	15 - 24	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336
Acetone; propan-2-one; propanone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8	12 - 15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2-methylpropan-1-ol; iso-butanol	(CAS-No.) 78-83-1 (EC-No.) 201-148-0 (EC Index-No.) 603-108-00-1	0.6 - 3	Flam. Liq. 3, H226 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336
n-butyl acetate	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1	0.6 - 3	Flam. Liq. 3, H226 STOT SE 3, H336
Methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X	0.6 - 3	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 STOT SE 1, H370
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]	(CAS-No.) 64742-95-6 (EC-No.) 265-199-0 (EC Index-No.) 649-356-00-4	< 0.6	Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304
Propan-2-ol; isopropyl alcohol; isopropanol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0	< 0.6	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2-methoxy-1-methylethyl acetate	(CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7	< 0.6	Flam. Liq. 3, H226
Zirconium 2-ethylhexanoate	(CAS-No.) 22464-99-9 (EC-No.) 245-018-1	< 0.6	Repr. 2, H361d

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X	( 3 =<C < 10) STOT SE 2, H371 ( 10 =<C < 100) STOT SE 1, H370

Full text of H-statements: see section 16



# MXS STAINLESS STEEL SPRAY PAINT

## Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 14/01/2019 Version: 0.0

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Get medical advice/attention if you feel unwell. IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : If eye irritation persists: Get medical advice/attention. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : Irritation.
- Symptoms/effects after eye contact : Serious damage to eyes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol.
- Explosion hazard : Pressurised container: May burst if heated.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.



# MXS STAINLESS STEEL SPRAY PAINT

## Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 14/01/2019 Version: 0.0

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

acetone; propan-2-one; propanone (67-64-1)		
EU	Local name	Acetone
EU	IOELV TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	500 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Turkey	Local name	Aseton
Turkey	OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Turkey	OEL TWA (ppm)	500 ppm
Turkey	Regulatory reference	12 Ağustos 2013 Tarihli ve 28733 Sayılı Resmî Gazete

### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Hand protection : Protective gloves

Eye protection : Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.

Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : No data available

Odour : No data available

Odour threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : No data available

Melting point : Not applicable

Freezing point : No data available

Boiling point : No data available

Flash point : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Vapour pressure : No data available

Relative vapour density at 20 °C : No data available

Relative density : No data available

Solubility : No data available

Log Pow : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : Pressurised container: May burst if heated.

Oxidising properties : No data available

Explosive limits : No data available



# MXS STAINLESS STEEL SPRAY PAINT

## Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 14/01/2019 Version: 0.0

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause damage to organs. May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

### MXS STAINLESS STEEL SPRAY PAINT

Vaporizer	Aerosol
-----------	---------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

### MXS STAINLESS STEEL SPRAY PAINT

Bioaccumulative potential	No additional information available
---------------------------	-------------------------------------

### 12.4. Mobility in soil

### MXS STAINLESS STEEL SPRAY PAINT

Mobility in soil	No additional information available
------------------	-------------------------------------

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No additional information available



# MXS STAINLESS STEEL SPRAY PAINT

## Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 14/01/2019 Version: 0.0






### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
1950	1950	1950	1950	1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

#### 14.6. Special precautions for user

##### - Overland transport

Classification code (ADR) : 5F  
 Special provisions (ADR) : 190, 327, 344, 625  
 Limited quantities (ADR) : 11  
 Excepted quantities (ADR) : E0  
 Packing instructions (ADR) : P207, LP200  
 Special packing provisions (ADR) : PP87, RR6, L2  
 Mixed packing provisions (ADR) : MP9  
 Transport category (ADR) : 2  
 Special provisions for carriage - Packages (ADR) : V14  
 Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12  
 Special provisions for carriage - Operation (ADR) : S2  
 Tunnel restriction code (ADR) : D

##### - Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
 Packing instructions (IMDG) : P207, LP200  
 Special packing provisions (IMDG) : PP87, L2  
 EmS-No. (Fire) : F-D  
 EmS-No. (Spillage) : S-U  
 Stowage category (IMDG) : None  
 Stowage and handling (IMDG) : SW1, SW22  
 Segregation (IMDG) : SG69



# MXS STAINLESS STEEL SPRAY PAINT

## Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 14/01/2019 Version: 0.0

### - Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### - Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

### - Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. National regulations

This product doesn't contain any substances that is controlled or prohibited for use according to the Regulation for Reduction of Ozone Depleting Substances published in the Official Journal numbered 27052 on November 12, 2008.

Regulatory reference	: Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015 Regulation on Test Methods that will be Applied to Determine the Physicochemical, Toxicological and Ecotoxicological Properties of Substances and Mixtures published in the Official Journal numbered 28848 on December 11, 2013 Regulation on Health and Safety Precautions When Working with Chemical Substances published in the Official Journal numbered 28733 on August 12, 2013 Regulation on Inventory and Control of Chemicals published in the Official Journal numbered 27092 on December 26, 2008 Regulation on Restriction and Prohibition of Hazardous Substances and Mixtures published in the Official Journal numbered 27092 on December 26, 2008 Communiqué on Detergents and Surfactants Used in Detergents published in the Official Journal numbered 27092 on December 26, 2008.
----------------------	--



# MXS STAINLESS STEEL SPRAY PAINT

## Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 14/01/2019 Version: 0.0

### SECTION 16: Other information

#### Full text of H-statements

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Press. Gas	Gases under pressure
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

#### Safety Data Sheet author's

Name : İrem BEKTAŞ KART  
Certificate number : GBF-A-0-2732  
Contact information : irem@bekkdanismanlik.com

#### SDS Turkey

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*